



Edelstahlwellenschlauch



ASSIWELL 066 1.4404 mit 1 Edelstahldraht-Umflechtung

Anschlüsse:

Beidseitig argon arc angeschweisster, flachdichtender Nippel aus Edelstahl 1.4404 mit Überwurfmutter Messing vernickelt. Leitungen SVGW geprüft und zugelassen.

DN	Uem	NL	Art.Nr.	VP CHF / Stk.
12	1/2"	300 mm	06.5101.5001	78.00
12	1/2"	500 mm	06.5101.5002	90.00
12	1/2"	700 mm	06.5101.5003	100.50
12	1/2"	1000 mm	06.5101.5004	110.00
16	3/4"	300 mm	06.5101.5007	97.50
16	3/4"	500 mm	06.5101.5008	105.00
16	3/4"	700 mm	06.5101.5009	118.00
16	3/4"	1000 mm	06.5101.5010	134.00
20	1"	300 mm	06.5101.5013	98.00
20	1"	500 mm	06.5101.5014	116.00
20	1"	700 mm	06.5101.5015	126.00
20	1"	1000 mm	06.5101.5016	142.00
25	1 1/4"	300 mm	06.5101.5019	105.00
25	1 1/4"	500 mm	06.5101.5020	130.00
25	1 1/4"	700 mm	06.5101.5021	152.00
25	1 1/4"	1000 mm	06.5101.5022	158.00
32	1 1/2"	300 mm	06.5101.5025	140.00
32	1 1/2"	500 mm	06.5101.5026	148.00
32	1 1/2"	700 mm	06.5101.5027	172.00
32	1 1/2"	1000 mm	06.5101.5028	204.00

ASSIWELL 066

DN (mm/ inch)	Typ type	Innendurch- messer internal diame- ter		Abmessungen dimensions			Biegeradius bend radius		Betriebsdruck working pressure bei / at 20 °C P max. (bar)	Gewicht weight
		D1 (mm)	Tol.± (mm)	D2 (mm)	D3 (mm)	Tol.± (mm)	Einmalige Bewegung single motion Rst (mm)	Häufige Bewegung several motion Rb (mm)		
8	U 0			12,2	-	-	16		13,0	
	U 1	8,4	0,1	-	13,6	-	32	124	132,0	
10	U 0			14,2	-	-	18		9,0	
	U 1	10,1	0,1	-	15,6	-	38	130	100,0	
12	U 0			16,9	-	-	20		7,0	
	U 1	12,5	0,2	-	18,3	-	45	140	70,0	
16	U 0			21,8	-	-	28		5,0	
	U 1	16,3	0,2	-	23,8	-	58	160	65,0	
20	U 0			26,6	-	-	32		3,0	
	U 1	20,3	0,2	-	28,6	-	70	170	43,0	
25	U 0			32,3	-	-	40		2,5	
	U 1	25,4	0,2	-	34,3	-	85	190	49,0	
32	U 0			41,1	-	-	50		2,0	
	U 1	34,3	0,2	-	43,0	-	105	260	35,0	
40	U 0			49,6	-	-	60		2,0	
	U 1	40,0	0,3	-	52,0	-	130	300	38,0	
50	U 0			60,5	-	-	70		1,0	
	U 1	50,5	0,3	-	62,4	-	160	320	26,0	

(Keine Erhebung des Betriebsdruck mit SF4)

Ihr Partner für Industrie und Handwerk

Götschi AG

Werkzeuge und Maschinen

Dornacherstrasse 380

4053 Basel

Telefon: 061 337 45 11 E-Mail: info@goetschi.ch

Telefax: 061 337 45 12 Internet: www.goetschi.ch

15 Kundenparkplätze

